

Specifications

Construction: Vinyl, PVC décor film, UV Coating

Edge Type: Beveled

Overall Thickness: 3mm

Wear Layer: 0.5mm (20mil)

Length: 48"

Width: 7"

Coverage per Carton: 34.55 ft²

Pieces per Carton: 14

Weight per Carton: 41 lbs.

Installation Method: Glue Down

Recommended Usage: Residential & Light Commercial

Underlayment Required: No



This product is protected by a 50 year residential/15 year light commercial warranty



This floor is easy to maintain



This product is waterproof and won't be affected by household spills

The Platinum Collection is one of our most popular vinyl floors. With a commercial warranty, a durable wear layer, and a selection of stunning colors this flooring is ideal for your home or office.

Features

- UV Resistant*
- Fire Resistant*
- Scratch Resistant*
- Slip Resistant*
- Stain Resistant*
- Fade Resistant*
- Hypoallergenic*
- Non Toxic*
- Mildew Resistant*
- Easy Maintenance*

Recommended Adhesive

Duvall K-PSA Pressure Sensitive Adhesive. Solvent Free formula. "Zero" calculated VOC. Resists Plasticizer Migration. Low Odor.

Technical Data

Manufacturing standard	EN 649	pass
Total thickness	EN 428	3.0mm
Thickness of wear layer	EN 429	0.5mm
Peeling strength of layers	EN 431	Pass
Size tile (L x W)	EN 427	187 x 1227mm
Sound, impact, reduction	EN ISO 717-2	>4.8 dB
Fire resistance	EN 13501-1	Bfl-S1
Dimension stability after exposure to heat	EN 434	< 0,10%
Colour fastness to light	ISO 105 B02	grade > 6
Static indentation		0.02mm
Flexibility	EN 435	pass
Abrasion resistance	EN 660	class T
Castor chair resistance	EN 425	pass
Slip resistance	EN 13893/DIN 51131	>= 0,3/ R10
Anti-sliding properties	class DS	μ = 0,59
Usage category	EN 685	32
Resistance to chemicals		pass
Light fastness	ISO 105-B02-3	> 6
Surface treatment		Semi-matt