

Specifications

Construction: Vinyl, Composite Core, Cork Backer, UV Coating + PVC Décor Film

Edge Type: Valinga

Overall Thickness: 8.5mm

Wear Layer: 0.5mm (20mil)

Length: 72"

Width: 8-7/8"

Coverage per Carton: 26.59 ft²

Pieces per Carton: 6

Weight per Carton: 48 lbs.

Installation Method: Floating

Recommended Usage: Residential & Light Commercial

Underlayment Recommended: Yes



This product is protected by a 50 year residential/10 year light commercial warranty



This floor is waterproof and won't be affected by household spills



This product is Floor Score Certified


Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance

Recommended Underlayment

- **WPCEVA** 1mm Black EVA Foam with 0.1mm black PE film
- **WPCSS** 1.5mm high density black foam with 0.1mm black PE film
- **WPCZS** 1.5mm Zero Slip foam

Technical Data



Peeling strength of layers	EN 431	Pass
Size tile(L x W)	EN 427	1830*225
Reaction to Fire	EN 13501-1	Class Bn-S1
Colour fastness to light	ISO 105 B02	Grade ≥6
Flexibility	EN 435	Pass
Abrasion resistance	EN 650	Class T
Castor chair resistance	EN 425	Pass
Slip resistance	EN 13893/DIN 51131	≥DS/R9
Anti-sliding properties	Class DS	pass
Light fastness	ISO 105-B02-3	> 6
temperature expansion rating	EN434	<0.25%

Accessories

MATCHING MOLDINGS AVAILABLE

