

## Specifications

Construction: Vinyl, Composite Core,  
UV Coating + PVC Décor Film

Edge Type: Square

Overall Thickness: 5.5mm

Wear Layer: 0.1mm (4mil)

Length: 48"

Width: 7"

Coverage per Carton: 37.82 ft<sup>2</sup>

Pieces per Carton: 16

Weight per Carton: 47 lbs.

IIC=58 / STC=62

IIC=66 / STC=52 (with 1.5mm pad)

Installation Method: Floating

Recommended Usage: Residential

Underlayment Recommended: Yes



This product is protected by a 15  
year residential warranty



This floor is waterproof and won't be  
affected by household spills



This product is Floor Score Certified


## Features

- |                     |                    |
|---------------------|--------------------|
| ✓ UV Resistant      | ✓ Fade Resistant   |
| ✓ Fire Resistant    | ✓ Hypoallergenic   |
| ✓ Scratch Resistant | ✓ Non Toxic        |
| ✓ Slip Resistant    | ✓ Mildew Resistant |
| ✓ Stain Resistant   | ✓ Easy Maintenance |

## Recommended Underlayment

- **WPCEVA** 1mm Black EVA Foam with 0.1mm black PE film
- **WPCSS** 1.5mm high density black foam with 0.1mm black PE film
- **WPCZS** 1.5mm Zero Slip foam

## Technical Data



Manufacturing standard	EN 649	pass
Total thickness	EN 428	5.5mm
Thickness of wear layer	EN 429	0.1mm
Peeling strength of layers	EN 431	Pass
Size file (L x W)	EN 427	179 x 1218mm
Sound impact reduction	EN ISO 717-2	>4.8 dB
Fire resistance	EN 13501-1	Bfl-S1
Dimension stability after exposure to heat	EN 434	< 0.10%
Colour fastness to light	ISO 105 B02	grade > 6
Static indentation		0.02mm
Flexibility	EN 435	pass
Abrasion resistance	EN 660	class T
Castor chair resistance	EN 425	pass
Slip resistance	EN 13893/DIN 51131	>= 0.3/ R10
Anti-sliding properties	class DS	μ = 0.59
Usage category	EN 685	21
Resistance to chemicals		pass
Light fastness	ISO 105-B02-3	> 6
Surface treatment		matt, Semi-matt

## Accessories

### MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding