

## Specifications

Construction: Birch Veneer, Eucalyptus Core

Edge Type: Micro Bevel

Overall Thickness: ½ inch

Wear Layer: 2mm

Janka Hardness Rating: 1260

Length: Random, 16"-48"

Width: 5"

Coverage per Carton: 26.25 ft<sup>2</sup>

Pieces per Carton: Random

Weight per Carton: 44 lbs.

Installation Method: Glue Down

Recommended Usage: Residential



This product is protected by a 25 year residential warranty



This product is Floor Score certified



This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

This floor comes in a selection of birch colors. The 2mm top layer creates durability and the light distress marks against rich color add a sleek yet rugged look.

## Features

- UV Resistant*
- Fade Resistant*
- Fire Resistant*
- Hypoallergenic*
- Scratch Resistant*
- Non Toxic*
- Slip Resistant*
- Mildew Resistant*
- Stain Resistant*
- Easy Maintenance*

## Recommended Adhesive



### Sika T21

All-in-One Wood Flooring Urethane Adhesive, Moisture Vapor and Sound Reduction Membrane



### Sika T35

Trowel-applied, Polyurethane Wood Flooring Adhesive

## Accessories

