

Specifications

Construction: High Density Fiberboard

Edge Type: Pressed Edge

Thickness: 12.3mm

Length: 48"

Width: 6-1/2"

Coverage per Carton: 17.05/17.33 ft²

Pieces per Carton: 8

Weight per Carton: 40 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes



This product is protected by a 25 year residential warranty



Abrasion Class 3 Rating works well in all areas of the home and can withstand normal household traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board. Formaldehyde is less than 0.05%

With pressed edges and rich tones, the Prestige Collection is definitely a sight to see.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance

Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



XPE



Felt



Rubber



1/4 Cork



1/2 Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding