

## Specifications

Construction: Vinyl, Composite Core, UV Coating + PVC Décor Film

Edge Type: Square

Overall Thickness: 5.5mm

Wear Layer: 0.1mm (4mil)

Length: 48"

Width: 7"

Coverage per Carton: 37.82 ft<sup>2</sup>

Pieces per Carton: 16

Weight per Carton: 54 lbs.

IIC=58 / STC=62

IIC=66 / STC=62 (with 1.5mm pad)

Installation Method: Floating

Recommended Usage: Residential

Underlayment Recommended: Yes



This product is protected by a 15 year residential warranty



This floor is waterproof and won't be affected by household spills

## Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


## Recommended Underlayment

- **WPCEVA** 1mm Black EVA Foam with 0.1mm black PE film
- **WPCSS** 1.5mm high density black foam with 0.1mm black PE film
- **WPCZS** 1.5mm Zero Slip foam

## Certifications

 <p>GREENGUARD PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818</p>	<p>GREENGUARD Certification ensures that a product has met some of the world's most rigorous and comprehensive standards for low emissions of volatile organic compounds (VOCs) into indoor air.</p>
 <p>floor score CERTIFIED BY SCS Global Services</p>	<p>FloorScore® is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives, and underlayments.</p>

## Accessories



PRODUCT SPECIFICATIONS			
Product	Overall Thickness	5.5mm (No Pad) (1.5mm lvt+4.0wpc)	
Dimensions	Width and Length	180mmW x 1220mmL	
Packaging (Per Carton)		16 Planks	37.82 Sq.Ft. 54.25 Lbs
Construction	Top Layers	High Definition Decor Film	
		Enhanced Polyurethane Coating	
		0.15mm Wear Layer	
	Core	5.0mm Limestone Composite: min. 45% stone, 0% wood, 100% Virgin Material	
	Density	1220kg/m <sup>3</sup> ±10%	
	Pad	No pad	
Bevel	No Bevel		
Installation	Floating Glueless		
Under Floor Heating	Approved - See installation manual for details.		
Warranty	15 years residential		
Static Load	ASTM F970	500PSI	
Heat Exposure Resistance F1700	ASTM F2199 modified(70°C) EN16511 modified (70°C)	≤0.15%	
Swelling after submersion	NALFA LF 01-2011	0.2% Class 4,	
Impact Insulation Class	ASTM E492-09	IIIC=58 / STC=62 With 1.5mm pad: IIC=66 / STC=62	
Castor Chair Resistance	ISO 4918	Pass	
Fire Rating	ASTM E648/ 662	Class I	
Wear Resistance	EN 13329 method A	Class 21,	
F1700	EN 16511	Class 21,	
Impact Resistance (Big Ball)	NALFA LF01-2011 EN 16511		
Impact Resistance (Small Ball)	NALFA LF01-2011		
Static coefficient of Friction	ASTM D2047	Dry: 0.5, Wet: 0.65	
Resistance to staining F1700	ASTM F925 NALFA LF01-2011	Pass Class 4,	
Chemical Composition			
VOC	FloorScore™	Pass California	
Ortho-phthalates	Prop 65	Not Detected / In Compliance	
Lead	CPSIA	None Detected	
Substances of Very High Concern (SVHC) (Mercury, Chromium VI, Cadmium, SCCp, Benzene, Xylene, Tributyltin, etc.)		Not Detected	